

Product Data Sheet

SUREBANDClear

Ideal for Acid / Caustic / EI15 Oil and Diesel mist prevention

Manufactured from All-PTFE materials (no fibreglass) comprising clear ETFE outer and multi-layered ETFE mesh inner. This material provides unparalleled chemical resistance. All our shields are tested on our hydrostatic pressure test facility, test certificates available on request.

The internal mesh is compressed against the flange and prevents direct and lateral spray. The liquid pressure inside is rapidly diffused, resulting in a safe drip-release.

SUREBAND*Clear* is very quick to install using heavy duty Velcro tabs which have been leak tested at various orifice sizes at pressure up to 75 Bar. It can be re-used in the event of a leak, thus providing a long term solution.

Specification

Band Material	:	ETFE
Mesh Material	:	ETFE
Fastener	:	Heavy Duty Velcro
Shear force	:	196 N
Max Temperature	:	200 Deg C
Flange Ratings	:	ANSI / DIN / many others
Pipe Sizes	:	15mm to 1200mm
Leak Detection	:	Visual Litmus Paper
Typical Applications	:	Acid, Bases, Oil

This product can also be made to fit valves and other nonstandard pipe joints, contact us for further information

Delivery

Most shield materials and sizes are available ex-stock. Call 01268 244369 or e-mail sales@flangeguards.com.







Revision date: 20th January 2021



LEADING MANUFACTURER AND SUPPLIER OF PIPE SAFETY SHIELDS

Flangeguards Ltd. Unit 5 Cranes Close, Basildon, Essex SS14 3JB United Kingdom